

/ DELFISCAN C90

IMAGING TECHNOLOGY

The Gryphon™ 4000 series represents the premium level of data collection devices from Datalogic ADC for general purpose applications. Designed with people in mind, the Gryphon™ I GD4400 imager blends advanced 2D reading with motion sensing technology, producing a user-friendly device with outstanding performance.

MODERN FEATURES FOR TODAY'S POS

Perfect for both handheld and presentation reading, the Gryphon I GD4400 imager features Datalogic's Motionix™ motion-sensing technology which detects the natural actions of the operator to automatically switch the scanner into the desired scanning mode. This technology works with or without the use of a stand, offering more operational choices. Both the aimer and sensor can be programmed to the user's desired preferences. User comfort is maximized with the Gryphon I GD4400 imager's steady, deep red illumination light. Easier on the eyes than competitive products with flicker illumination, the highly visible 4-Dot aimer defines a precise reading zone and reduces accidental reads. The aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.

SIMPLE TO USE AND DEPLOY

The Gryphon I GD4400 imager provides snappy reading performance on all common 1D and 2D codes as well as postal, stacked and composite codes like PDF417. High Density (HD) models are also available for reading smaller, condensed codes. For mobile marketing or ticketing applications, this imager also offers excellent performance when reading bar codes from mobile devices.

The Gryphon I GD4400 2D omnidirectional reader eliminates the need for separate equipment with signature capture and document scanning capabilities. Its enhanced optics offer improved motion tolerance and high speed imaging to read fast moving codes

DECODING CAPABILITY

1D / LINEAR CODES Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.

2D CODES Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code

POSTAL CODES Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet;



FEATURES

- Motionix™ motion-sensing technology for seamless reading mode transitions
- Highly visible 4-Dot aimer with center cross for targeted scanning
- Omnidirectional reading
- Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads 1D, 2D and postal codes plus stacked and composite codes
- Multi-interface options: RS-232 / IBM 46XX / USB or RS-232 / USB / Keyboard Wedge / Wand
- Datalogic's patented 'Green Spot' for good-read feedback
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI
- Retail - Point of Sale
- Light Manufacturing
- Access Control, Transportation and Entertainment
- Commercial Services: Postal, Banks, Public Administration, Utilities

/ DELFIACAN C90

TECHNICAL DATA:

DECODING CAPABILITY

1D / LINEAR CODES Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.

2D CODES Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code

POSTAL CODES Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)

STACKED CODES EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

ELECTRICAL

CURRENT Operating (Typical): GD4410: < 170 mA @ 5 VDC; GD4430 < 160 mA @ 5 VDC Standby/Idle (Typical): 65 mA @ 5 VDC

INPUT VOLTAGE GD4410: 4.0 - 14.0 VDC; GD4430: 4.2 - 5.25 VDC

ENVIRONMENTAL

AMBIENT LIGHT 0 - 100,000 lux

DROP RESISTANCE Withstands repeated drops from 1.8 m / 5.9 ft onto a concrete surface.

ESD PROTECTION (AIR DISCHARGE) 16 kV

HUMIDITY (NON-CONDENSING) 5 - 95%

PARTICULATE AND WATER SEALING IP52

TEMPERATURE Operating: 0 to 50 °C / 32 to 122 °F

Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES

GD4410: RS-232 / IBM 46XX / USB Multi-Interface GD4430: RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE Black; White

DIMENSIONS 18.1 x 7.1 x 10.0 cm / 7.1 x 2.8 x 3.9 in

WEIGHT 195.0 g / 6.9 oz

READING PERFORMANCE

IMAGE CAPTURE Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2

IMAGER SENSOR Wide VGA: 752 x 480 pixels

LIGHT SOURCE Aiming: 650 nm VLD

MOTION TOLERANCE 25 IPS

PRINT CONTRAST RATIO (MINIMUM) 25%

READING ANGLE Pitch: +/- 40°; Roll (Tilt): 180°; Skew (Yaw): +/- 40°

READING INDICATORS Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED

RESOLUTION (MAXIMUM) High Density (HD): 1D Linear: 0.077 mm / 3 mils;

Data Matrix: 0.127 mm / 5 mils; PDF417: 0.102 mm / 4 mils

Standard Range (SR): 1D Linear: 0.102 mm / 4 mils;

Data Matrix: 0.178 mm / 7 mils; PDF417: 0.102 mm / 4 mils

READING RANGES

TYPICAL DEPTH OF FIELD Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

GD4400 Standard Range (SR) GD4400 High Density

(HD) Code 39: 5 mils: 4.0 to 19.0 cm / 1.6 to 7.5 in Code

39: 3 mils: 2.4 to 9.1 cm / 0.9 to 3.6 in

Code 39: 10 mils: 1.0 to 30.0 cm / 0.4 to 11.8 in Code 39:

5 mils: 0.8 to 11.3 cm / 0.3 to 4.5 in

Data Matrix: 10 mils: 2.0 to 16.0 cm / 0.8 to 6.3 in Data

Matrix: 5 mils: 2.8 to 6.1 cm / 1.1 to 2.4 in

Data Matrix: 15 mils: 0 to 23.6 cm / 0 to 9.3 in EAN-13: 13

mils: 1.1 to 17.2 cm / 0.4 to 6.8 in

EAN-13: 13 mils: 1.5 to 40.0 cm / 0.6 to 15.7 in PDF417:

4 mils: 1.8 to 6.8 cm / 0.7 to 2.7 in

PDF417: 10 mils: 0.5 to 22.0 cm / 0.2 to 8.6 in PDF417:

10 mils: 0 to 14.3 cm / 0 to 5.6 in

QR Code: 10 mils: 3.0 to 12.5 cm / 1.2 to 4.9 in QR

Code: 6.7 mils: 2.1 to 4.2 cm / 0.8 to 1.7 in

SAFETY & REGULATORY

AGENCY APPROVALS The product meets necessary safety and regulatory approvals for its intended use.

ENVIRONMENTAL COMPLIANCE Complies to China RoHS; Complies to EU RoHS

LASER CLASSIFICATION Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

UTILITIES

DATALOGIC ALADDIN™ Datalogic Aladdin configuration program is available for download at no charge.

OPOS / JAVAPOS JavaPOS Utilities are available for download at no charge.

OPOS Utilities are available for download at no charge.

REMOTE HOST DOWNLOAD Lowers service costs and improves operations: GD4410

WARRANTY

WARRANTY 5-Year Factory Warranty